

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/095800 A1

(51) International Patent Classification⁷: **F04B 49/06**

(21) International Application Number:
PCT/GB2005/001235

(22) International Filing Date: 31 March 2005 (31.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0407297.1 31 March 2004 (31.03.2004) GB

(71) Applicant (for all designated States except US):
ARTEMIS INTELLIGENT POWER LIMITED
[GB/GB]; Sanderson Building, Mayfield Road, Edinburgh
EH9 3JL (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **CALDWELL, Niall,**


James [GB/GB]; 2F2 5 Balcarres Street, Edinburgh EH10 5JB (GB). **RAMPEN, William, Hugh, Salvin** [GB/GB]; 1 Merchiston Crescent, Edinburgh EH10 5AN (GB). **STEIN, Uwe, Bernhard, Pascal** [DE/GB]; 19 Hope Lane North, Edinburgh EH15 2PT (GB).

(74) Agent: **HANSON, William, Bennett;** Bromhead Johnson, Kingsbourne House, 229-231 High Holborn, London WC1V 7DP (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: FLUID-WORKING MACHINE WITH DISPLACEMENT CONTROL



(57) Abstract: A fluid-working machine has working chambers (4), each of which is connected to a fluid commutating means (2) which alternately connects the working chamber to either of two fluid manifolds (A, B). An electronically controlled valve (1) is inserted into the flow path between each chamber (4) and the commutating means. This valve is commanded by a controller (6) receiving an input signal of the phase angle of the shaft (5) of the machine or at least one electronic pulse per revolution which informs the controller that the shaft is passing a known phase angle. The valve (1) allows overriding of fixed mechanical commutation by closing the valve cyclically, synchronised with the angular position of the shaft (5). Thus the controller (6) is able to vary the time-averaged fluid flow into or out of the machine by varying the proportion of chambers (4) which are isolated from or connected to the mechanical commutating means (2), to control the torque, speed, and/or fluid flow into and out of the machine.



(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*